



Western Australia

Health (Miscellaneous Provisions) Act 1911

Construction Camp Regulations

Construction Camp Regulations

Contents

Part I — Preliminary

1.	Citation	1
4.	Onus	1

Part II — General regulations for construction camps

5.	Definitions	2
6.	Application	3
7.	Doors and light in sleeping quarters	3
8.	Air space in sleeping quarters	3
9.	Ventilation of sleeping quarters	4
10.	Space between beds	4
11.	Cooking prohibited in sleeping quarters	4
12.	Ventilation of kitchen	5
13.	Kitchen stoves	6
14.	Kitchen protection against insects	6
15.	Kitchen floor	6
16.	Kitchen facilities	6
17.	Kitchen cleansing	7
18.	Dining room space	7
19.	Ventilation of dining room	7
20.	Construction and lighting of dining room	8
21.	Dining room insect protection	8
22.	Tables	8
23.	Sanitary and ablutionary facilities	8
24.	Closets	9
25.	Plumbing standards	9
26.	Laundry facilities	9

27.	Water supply	10
Part III — Caravans used in construction camps		
28.	Definitions	11
29.	Floor areas in residential caravans	12
30.	Ceiling heights in residential caravans	13
31.	Toilet compartments in relation to food preparation	13
32.	Separate sleeping compartments	13
33.	Sleeping compartment dimensions	13
34.	Fly wire	13
35.	Dining caravans	14
36.	Kitchen caravans	14
37.	Office caravan	14
38.	Ablutionary and sanitary caravans	14
39.	Materials used in caravan construction	15
40.	Internal linings	15
41.	Design and construction	16
42.	Artificial light	17
43.	Residential caravans	17
44.	Internal equipment	18
45.	Fixed ventilation	19
46.	Adjustable ventilation	20
Part IV — Offences and penalties		
47.	Offences and penalties	21
Notes		
	Compilation table	22
Defined terms		

Western Australia

Health (Miscellaneous Provisions) Act 1911

Construction Camp Regulations

Part I — Preliminary

1. Citation

These regulations may be cited as the *Construction Camp Regulations*¹.

[2. *Omitted under the Reprints Act 1984 s. 7(4)(d).*]

[3. *Omitted under the Reprints Act 1984 s. 7(4)(c).*]

4. Onus

The onus of complying with these regulations shall unless otherwise provided rest with the occupier of the construction camp.

Part II — General regulations for construction camps

5. Definitions

In these regulations, unless the context otherwise requires —

artificial light means light sufficient to illuminate the entire room at 54 lumens per square metre of general illumination, measured on a horizontal plane 915 millimetres above the floor;

construction camp means any camp used for a duration of more than 6 months though not necessarily in the one location, for the accommodation of a work force of more than 25 persons in conjunction with —

- (a) the construction of a railway line or siding;
- (b) the construction, structural alteration or demolition of —
 - (i) a building;
 - (ii) a dock, wharf, jetty, pier, breakwater, tunnel, dam, viaduct, reservoir, pipeline, gasholder; and
 - (iii) waterworks or sewerage works;
- (c) the preparation of an area for mining operations; and
- (d) any other work that requires a temporary resident work force,

but does not include —

- (e) camps used for defence purposes; and
- (f) wayside camps of drovers or teamsters;

dining room means a dining room in any construction camp to which this Part applies;

effective air conditioning means the distribution of filtered air into an enclosed space at controlled temperatures and humidity and **effectively air conditioned** has a corresponding meaning;

kitchen means a kitchen in any construction camp to which this Part applies;

occupier means a person having the charge, management or control of premises, and where 2 or more persons share or jointly have the charge, management or control of premises, each of those persons;

sleeping quarters means sleeping quarters in any construction camp to which this Part applies.

*[Regulation 5 amended: Gazette 18 Nov 1970 p. 3586;
3 May 1974 p. 1428.]*

6. Application

This Part does not apply to caravans in construction camps.

7. Doors and light in sleeping quarters

Every sleeping quarters shall —

- (a) have at least one door of at least 760 millimetres in width and 1.98 metres in height; and
- (b) be provided with artificial light.

[Regulation 7 amended: Gazette 3 May 1974 p. 1428.]

8. Air space in sleeping quarters

- (1) Every sleeping quarters shall contain not less than 11 cubic metres of air space calculated for each person who sleeps in the quarters, except where the sleeping quarters are transportable units which shall contain not less than 9 cubic metres of air space for each such person.
- (2) Where transportable units used as sleeping quarters in any area north of the 26th parallel of latitude or in any other area specified by the Minister by notice published in the *Gazette*, contain less than 11 cubic metres of air space for each person who sleeps in the quarters, effective air conditioning shall be installed in those sleeping quarters.

[Regulation 8 inserted: Gazette 18 Nov 1970 p. 3586; amended: Gazette 3 May 1974 p. 1428.]

9. Ventilation of sleeping quarters

Every sleeping quarters shall be ventilated —

- (a) by the provision of a window or windows, which when opened, either singly or in the aggregate, provide an open space —
 - (i) that has a minimum area of 0.5 square metre for every 10 square metres of floor area;
 - (ii) the highest part of which is within 460 millimetres of the ceiling line; and
 - (iii) that provides direct uncontrolled ventilation to the external air;

or

- (b) by permanent ventilation consisting of 0.015 square metre of uncontrolled ventilation for each 10 square metres of floor area; or
- (c) by a system of mechanical ventilation giving not less than 6 changes of air per hour.

[Regulation 9 amended: Gazette 3 May 1974 p. 1428.]

10. Space between beds

Every sleeping quarters shall have a space of not less than 810 millimetres between each bed.

[Regulation 10 amended: Gazette 18 Nov 1970 p. 3586; 3 May 1974 p. 1428.]

11. Cooking prohibited in sleeping quarters

No person shall be permitted to prepare or partake of a meal in any sleeping quarters, except when a person is confined to those quarters by ill-health.

12. Ventilation of kitchen

- (1) Every kitchen shall be ventilated by one of the following methods —
- (a) by natural ventilation consisting of —
 - (i) one or more windows placed in an external wall, so constructed that portion of the windows equal to at least one-twentieth of the floor area of the room can be opened and portion of each such window extends to at least 1.98 metres above the floor level; and
 - (ii) by registers, vents, cowls or ducts, fixed in or near the ceiling boxed in and having a baffle of 50 millimetres clear above the boxing and extending 75 millimetres beyond it on all sides, so as to provide an effective airway of not less than 4 000 square millimetres for each one square metre of floor area;
- or
- (b) by a system of mechanical ventilation giving not less than 15 complete changes of air per hour.
- (2) For the purposes of subregulation (1)(a)(i), where a kitchen is fitted with a door —
- (a) the upper half of which moves independently of the lower half;
 - (b) which is fitted in an external wall; and
 - (c) which extends to at least 1.98 metres above floor level,

the area of the upper half of that door may be regarded as the opening portion of a window.

*[Regulation 12 amended: Gazette 3 May 1974 p. 1428-9;
12 Jul 1974 p. 2597.]*

13. Kitchen stoves

Every stove in a kitchen shall have a hood connected to a ventilation shaft sufficient to carry away all steam and cooking odours.

14. Kitchen protection against insects

- (1) The windows, doorways and other openings in every kitchen shall be screened with a fine mesh to exclude the ingress of flies and other insects.
- (2) Food in any kitchen not being prepared and not in the refrigerator shall be kept in fly proof cupboards.

15. Kitchen floor

Every kitchen floor shall be of an impervious material.

16. Kitchen facilities

Every kitchen shall be equipped with —

- (a) a stainless steel sink for dishwashing;
- (b) a stainless steel wash trough for washing pots and larger kitchen utensils;
- (c) a handbasin supplied with hot and cold water, soap, nailbrush and disposable paper towels;
- (d) an adequate supply of hot water available at all times;
- (e) food preparation tables with a smooth impervious washable surface of a material other than lino;
- (f) adequate refrigerated storage for keeping perishable foods;
- (g) a sufficient number of rubbish receptacles with a smooth impervious surface and tight fitting lid, for the reception of food scraps; and
- (h) artificial light.

17. Kitchen cleansing

- (1) Every kitchen and all its facilities shall be maintained in a clean and efficient condition.
- (2) To enable cleansing to be carried out in the kitchen —
 - (a) stoves, not sealed against a wall, shall be positioned at least 75 millimetres clear of the wall;
 - (b) benches and fixtures not built into the floor, shall be at least 380 millimetres clear of the floor; and
 - (c) all cupboards and other fixtures and all walls and ceilings shall have smooth impervious washable surfaces.

[Regulation 17 amended: Gazette 3 May 1974 p. 1429.]

18. Dining room space

Every dining room shall contain at least one square metre of space for each person it accommodates at any one time.

[Regulation 18 amended: Gazette 18 Nov 1970 p. 3586; 3 May 1974 p. 1429.]

19. Ventilation of dining room

Every dining room shall be ventilated —

- (a) by controllable ventilation and by permanent ventilation consisting of 0.015 square metre of uncontrolled ventilation for every 10 square metres of area;
- (b) by a system of mechanical ventilation giving not less than 8 complete changes of air per hour; or
- (c) by effective air conditioning.

[Regulation 19 amended: Gazette 18 Nov 1970 p. 3586; 3 May 1974 p. 1429.]

20. Construction and lighting of dining room

Every dining room —

- (a) shall be lined and ceiled;
- (b) shall have walls with a smooth impervious washable surface to a height of at least 1.8 metres;
- (c) shall have floors of an impervious material;
- (d) shall have window areas of one square metre for each 10 square metres of floor space, or be effectively air conditioned;
- (e) shall be provided with artificial light.

*[Regulation 20 amended: Gazette 18 Nov 1970 p. 3587;
3 May 1974 p. 1429.]*

21. Dining room insect protection

The windows, doorways and other openings in the dining room shall be screened with a fine mesh or by some other physical means to exclude the ingress of flies and other insects.

[Regulation 21 amended: Gazette 18 Nov 1970 p. 3587.]

22. Tables

Every dining room —

- (a) shall have tables with a smooth impervious washable surface of a material other than lino; and
- (b) shall have at least 610 millimetres of space at a dining table for every person it accommodates.

[Regulation 22 amended: Gazette 3 May 1974 p. 1429.]

23. Sanitary and ablutionary facilities

Every construction camp shall provide —

- (a) for males —
 - (i) one closet to every 15 employees;

- (ii) one urinal stall or 535 millimetres of urinal space at a urinal stall for every 20 employees;
 - (iii) one shower to every 15 employees; and
 - (iv) either one wash basin to every 15 employees or an equivalent trough with taps spaced 610 millimetres apart;
- (b) for females —
- (i) one closet to every 10 employees;
 - (ii) one shower to every 15 employees; and
 - (iii) either one wash basin to every 15 employees or an equivalent trough with taps spaced 610 millimetres apart.

[Regulation 23 amended: Gazette 3 May 1974 p. 1429.]

24. Closets

In every construction camp —

- (a) closets shall be connected to the water carriage system of disposal wherever possible;
- (b) where a closet is not connected to the water carriage system of disposal it shall be so constructed as to be completely fly proof.

25. Plumbing standards

All plumbing fixtures and fittings at a construction camp shall be in accordance with the requirements and standards applicable under the *Water Services Act 2012* and the *Plumbers Licensing and Plumbing Standards Regulations 2000*.

[Regulation 25 amended: Gazette 14 Nov 2013 p. 5031.]

26. Laundry facilities

- (1) Unless industrial laundry facilities are provided, every construction camp shall be provided with washing units to the following scale:

Construction Camp Regulations

Part II General regulations for construction camps

r. 27

Up to 100 persons — 1 unit to 10 persons.

Over 100 up to 200 persons — 1 unit to 12 persons.

Over 200 up to 300 persons — 1 unit to 15 persons.

Over 300 up to 500 persons — 1 unit to 20 persons.

Over 500 persons — 1 unit to 30 persons.

One washing unit consists of a copper and 2 troughs or a washing machine and one trough.

- (2) Where a washing machine is provided it must be connected to a hot water supply or have its own element capable of heating the water.
- (3) Clothes hoist or lines shall be provided in sufficient quantity to cater for the needs of the employees.

[Regulation 26 amended: Gazette 18 Nov 1970 p. 3587.]

27. Water supply

- (1) A sufficient supply of potable water for drinking purposes shall be provided at every construction camp.
- (2) All tanks and vessels used for the storage of drinking water shall be so constructed and covered as to prevent water stored therein from becoming polluted or contaminated.

Part III — Caravans used in construction camps

28. Definitions

In this Part, unless the context otherwise requires —

ablutionary or sanitary caravan means a structure with either fixed or retractable wheels and axles, designed for use as an ablutionary or sanitary block, so constructed as to be movable by towing and used in a construction camp;

artificial light means light sufficient to illuminate the entire room at 54 lumens per square metre of general illumination, measured on a horizontal plane 915 millimetres above the floor;

construction camp means any camp used for a duration of more than 3 months though not necessarily in the one location, for the accommodation of a work force of more than 25 persons in conjunction with —

- (a) the construction of a railway line or siding;
- (b) the construction, structural alteration or demolition of —
 - (i) a building;
 - (ii) a dock, wharf, jetty, pier, breakwater, tunnel, dam, viaduct, reservoir, pipeline, gasholder; and
 - (iii) waterworks or sewerage works;
- (c) the preparation of an area for mining operations; and
- (d) any other work that requires a temporary resident work force,

but does not include —

- (e) camps used for defence purposes; and
- (f) wayside camps of drovers or teamsters;

dining caravan means a structure with either fixed or retractable wheels and axles, designed for use as a dining room, so constructed as to be movable by towing, and used in a construction camp;

kitchen caravan means a structure with either fixed or retractable wheels and axles, designed for use as a kitchen, so constructed as to be movable by towing and used in a construction camp;

office caravan means a structure with either fixed or retractable wheels and axles, designed for use as an office, so constructed as to be movable by towing, and used in a construction camp;

residential caravan means a structure with either fixed or retractable wheels and axles, designed for use as a dwelling for human occupation, so constructed as to be movable by towing, and used in a construction camp;

sleeping caravan means a structure with either fixed or retractable wheels and axles, designed for use as sleeping compartments for human occupation, so constructed as to be movable by towing, and used in a construction camp;

toilet compartment means a compartment designed to accommodate a chemical closet or a water closet used in a construction camp.

*[Regulation 28 erratum: Gazette 26 Jun 1970 p. 1845;
amended: Gazette 3 May 1974 p. 1429.]*

29. Floor areas in residential caravans

- (1) Residential caravans shall have a floor area of not less than 7.4 square metres and the total floor area shall be ascertained from external measurements taken at a height of 460 millimetres above floor level.
- (2) A floor area of 3.7 square metres per person shall be provided for each adult or child over 10 years of age.
- (3) A floor area of 1.85 square metres shall be provided for each of the first 2 children under 10 years of age and 3.7 square metres each for any children under 10 years of age in excess of 2.

*[Regulation 29 amended: Gazette 16 Dec 1971 p. 5225;
3 May 1974 p. 1429.]*

30. Ceiling heights in residential caravans

The average ceiling height of a residential caravan shall not be less than 1.93 metres.

[Regulation 30 amended: Gazette 20 Apr 1971 p. 1189; 16 Dec 1971 p. 5225; 3 May 1974 p. 1429.]

31. Toilet compartments in relation to food preparation

A toilet compartment shall not open directly into that part of a caravan used for food preparation.

32. Separate sleeping compartments

- (1) Except for married couples, de facto partners and children under 10 years of age, there shall be separate sleeping compartments for males and females.
- (2) Every sleeping compartment for an adult shall be at least 1.9 metres in one plan dimension.

[Regulation 32 amended: Gazette 3 May 1974 p. 1429; 30 Jun 2003 p. 2598.]

33. Sleeping compartment dimensions

- (1) The dimensions of each sleeping compartment shall be such that there is 5 cubic metres for each person intended to be accommodated therein.
- (2) Each sleeping compartment shall have a locker or wardrobe for storage of clothes.

[Regulation 33 amended: Gazette 3 May 1974 p. 1429.]

34. Fly wire

The windows, doorways and other openings in dining and kitchen caravans shall be screened with fine mesh to exclude the ingress of flies and other insects.

35. Dining caravans

Every dining caravan shall have —

- (a) tables with a smooth impervious washable surface; and
- (b) at least 560 millimetres of space at a dining table for every person it accommodates.

[Regulation 35 amended: Gazette 3 May 1974 p. 1429.]

36. Kitchen caravans

(1) Every kitchen caravan shall be equipped with —

- (a) cooking facilities complying with regulation 44(d);
- (b) a double bowl stainless steel sink for dish-washing;
- (c) a handbasin supplied with hot and cold water, soap, nail-brush and disposable paper towels;
- (d) food preparation tables or benches with a smooth impervious washable surface;
- (e) adequate refrigeration storage for keeping perishable foods;
- (f) a sufficient number of rubbish receptacles with a smooth impervious surface and tight fitting lid, for the reception of food scraps; and
- (g) artificial light.

(2) Food in a kitchen caravan not being prepared and not in a refrigerator shall be kept in fly proof cupboards or containers.

37. Office caravan

In addition to office fittings, an office caravan may be fitted with a separate sleeping compartment complying with the requirements set out in regulation 33.

38. Ablutionary and sanitary caravans

(1) Where no fixed ablutionary and sanitary facilities are provided in a construction camp, ablutionary and sanitary caravans shall be used.

- (2) Ablutionary and sanitary caravans shall be fitted with water closets or chemical closets, showers, and wash basins in accordance with the requirements of regulation 23.
- (3) All plumbing fixtures and fittings shall be in accordance with the requirements and standards applicable under the *Water Services Act 2012* and the *Plumbers Licensing and Plumbing Standards Regulations 2000*.
- (4) Provision shall be made on the outlets of wash basins and showers for connection to an external method of liquid waste disposal.

*[Regulation 38 amended: Gazette 18 Nov 1970 p. 3587;
14 Nov 2013 p. 5032.]*

39. Materials used in caravan construction

- (1) All materials used in the construction of a caravan to which these regulations apply shall be of a suitable nature and quality for the purposes for which they are used and the methods of using the materials shall be according to accepted practice in the trade.
- (2) The materials used for the construction of the outer skin of a caravan used in a construction camp, shall not be inferior to those faces on which the effective spread of flames neither exceeds 305 millimetres during the first 1½ minutes, nor exceed 840 millimetres after 10 minutes.

[Regulation 39 amended: Gazette 3 May 1974 p. 1430.]

40. Internal linings

- (1) In a caravan used in a construction camp, the requirements for internal linings adjacent to any appliance which gives off heat shall be in accordance with the following standards —
 - (a) for solid fuel appliances B.S. Code of Practice CP. 340;
 - (b) for butane or propane gas Australian Standard CB20-1971 S.A.A. L.P. Gas Code; and

r. 41

(c) for electricity S.A.A. Code C.C.7.

- (2) Linings not referred to in subregulation (1) shall be in accordance with the Code of Practice and linings outside the areas of the Code of Practice shall, when finished, have surfaces not inferior to that required for the outer skin by regulation 39 and finishes based on nitrocellulose shall not be used.

[Regulation 40 amended: Gazette 16 Dec 1971 p. 5225.]

41. Design and construction

A caravan used in a construction camp shall be so designed and constructed that —

- (a) the structure shall be capable of sustaining and transmitting the dead load, imposed loads and horizontal and inclined forces to which it may be subjected in the service in which it is used;
- (b) the external construction of the caravan shall adequately resist the penetration of weather and dampness;
- (c) the external walls, roof and floor shall be of such materials and be so constructed, excluding glazed areas, that the thermal transmittance co-efficient to external surfaces is not more than 0.30;
- (d) condensation on the surface of the inner walls and partitions is avoided without the necessity for lowering the inside temperature or increasing the ventilation beyond the levels required for health and comfort;
- (e) every living compartment shall be provided with windows or skylights, the total area of which shall be not less than one-tenth the floor area of that compartment;
- (f) the roof shall discharge rainwater clear of windows and doors;
- (g) any fixed partitions separating sleeping compartments from other parts of the caravan together with hinged or sliding doors, shall for the purpose of obtaining some

- degree of fire protection, completely separate the 2 compartments between which they are used;
- (h) each separate compartment (other than a toilet compartment, shall be provided with a satisfactory, means of escape by —
- (i) a door of not less than 560 millimetres clear opening;
 - (ii) an escape panel of not less than 0.4 square metre clear opening with sides of not less than 460 millimetres and with its lower edge preferably not more than 760 millimetres above floor level, but never more than 915 millimetres above floor level; or
 - (iii) a window which, gives direct access to the open air in the event of fire and top hinged windows shall open through at least 70° and shall automatically stay full open until closed manually;
- (i) where it is a residential caravan there shall be at least 2 access doors spaced well apart or one door and adequate escape hatches, the door or doors shall open outwards and be of not less than 560 millimetres clear opening and shall be on the near side of the caravan and be hinged to the front.

[Regulation 41 amended: Gazette 3 May 1974 p. 1429-30.]

42. Artificial light

Every caravan used in a construction camp shall have means of providing artificial light either by gas or electricity.

43. Residential caravans

Every residential caravan shall be equipped with —

- (a) adequate cooking facilities;
- (b) a fixed sink, the waste pipe of which shall discharge outside the caravan;

- (c) an adequate food storage cupboard; and
- (d) a refrigerator.

44. Internal equipment

The installation of internal equipment in a caravan used in a construction camp shall where applicable comply with the following standards:

- (a) Any electrical installations shall comply with S.A.A. Code No. C.C.7. — Wiring of Caravans and Caravan Parks.
- (b) Any installation for the use of propane or butane gas shall comply with Australian Standard CB20-1971 S.A.A. L.P. Gas Code (1956).
- (c) Light fittings shall comply with S.A.A. Code C.C.7. for electricity and Australian Standard CB20-1971 S.A.A. L.P. Gas Code for gas.
- (d) Electrical cooking appliances shall comply with the S.A.A. Code No. C.C.7. — Wiring of Caravans and Caravan Parks and gas burning cooking appliances shall comply with Australian Standard CB20-1971 S.A.A. L.P. Gas Code.
- (e) All appliances shall be heat insulated from any combustible part of the caravan in the manner required in the Australian Standard CB20-1971 S.A.A. L.P. Gas Code and a shield of non-combustible material shall be provided over the exposed vertical surface adjacent to the immediately above any hotplate to a height of not less than 305 millimetres and extending beyond the sides of the appliance to a distance of not less than 405 millimetres.
- (f) Water heating appliances shall comply with Australian Standard CB20-1971 S.A.A. L.P. Gas Code for butane or propane gas S.A.A. Code C.C.7. for electricity and B.S. Code of Practice CP. 340 for solid fuel.

- (g) Chemical closets shall comply with the requirements of British Standard 2081 — Portable closets for use with chemicals.
- (h) Flushing water closets shall have provision on the pan outlet for connection to an external drainage system and shall be fed from a cold water storage cistern on the site distribution system via a flushing cistern complying with the requirements and standards applicable under the *Water Services Act 2012* and the *Plumbers Licensing and Plumbing Standards Regulations 2000*.
- (i) Boxed in compartments and cupboards shall be easily accessible for cleaning purposes.

[Regulation 44 amended: Gazette 16 Dec 1971 p. 5225; 3 May 1974 p. 1430; 14 Nov 2013 p. 5032.]

45. Fixed ventilation

Fixed ventilation shall be provided in caravans used in construction camps —

- (a) at the base of cookers and hotplates to ensure complete combustion of the fuel;
- (b) overhead, to remove products of combustion and cooking smells;
- (c) in gas container lockers in accordance with the requirements of Australian Standard CB20-1971 S.A.A. L.P. Gas Code;
- (d) in solid fuel fire installations in accordance with the requirements of B.S. Code of Practice CP. 340;
- (e) in food storage cupboards and lockers equally at the bottom and the top, each vent having a nett minimum area of 450 square millimetres per cubic metre of interior volume, calculated on the open space when the vents are covered with a vermin proof shield and shelves shall be so designed as to permit the passage of a current of air from the bottom vent to the top one;

r. 46

- (f) in totally enclosed fold-away beds, to permit a flow of air, but vents should not communicate directly with the air outside the caravan;
- (g) in wardrobes and bedlockers, to permit a flow of air from the bottom to the top, between ventilators, but vents should not communicate directly with the air outside the caravan;
- (h) in toilet compartments, at floor level near the chemical closet or water closet pan, and shall have not less than 2 900 square millimetres effective opening.

*[Regulation 45 amended: Gazette 16 Dec 1971 p. 5225;
3 May 1974 p. 1430.]*

46. Adjustable ventilation

In addition to permanent ventilation, adjustable ventilation shall be installed, in caravans used in construction camps, either in the roof or at a high level, in small bedrooms, over cookers and hot plates and in the toilet compartment to cater for adverse conditions requiring windows to be shut.

Part IV — Offences and penalties

[Heading inserted: Gazette 14 Oct 1988 p. 4160.]

47. Offences and penalties

- (1) A person who contravenes a provision of these regulations commits an offence and is liable to —
 - (a) a penalty which is not more than \$1 000 and not less than —
 - (i) in the case of a first offence, \$100;
 - (ii) in the case of a second offence, \$200; and
 - (iii) in the case of a third or subsequent offence, \$500;
 - and
 - (b) if that offence is a continuing offence, a daily penalty which is not more than \$100 and not less than \$50.

[Regulation 47 inserted: Gazette 14 Oct 1988 p. 4160.]

Notes

- ¹ This is a compilation of the *Construction Camp Regulations* and includes the amendments made by the other written laws referred to in the following table. The table also contains information about any reprint.

Compilation table

Citation	Gazettal	Commencement
<i>Construction Camp Regulations</i>	16 Jun 1970 p. 1668-75	16 Jun 1970
Untitled regulations	18 Nov 1970 p. 3586-7	18 Nov 1970
Untitled regulations	20 Apr 1971 p. 1188-9	20 Apr 1971
Untitled regulations	16 Dec 1971 p. 5225	16 Dec 1971
Untitled regulations	3 May 1974 p. 1428-30	3 May 1974
Untitled Regulations	12 Jul 1974 p. 2597	12 Jul 1974
Reprint of the <i>Construction Camp Regulations</i> as at 11 Oct 1985 in <i>Gazette</i> 29 Oct 1985 p. 4167-82 (includes amendments listed above)		
<i>Health (Offences and Penalties) Amendment Regulations 1988 Pt. 2</i>	14 Oct 1988 p. 4160-3	14 Oct 1988
<i>Equality of Status Subsidiary Legislation Amendment Regulations 2003 Pt. 8</i>	30 Jun 2003 p. 2581-638	1 Jul 2003 (see r. 2 and <i>Gazette</i> 30 Jun 2003 p. 2579)
Reprint 2: The <i>Construction Camp Regulations</i> as at 5 Dec 2003 (includes amendments listed above) (correction in <i>Gazette</i> 13 Jan 2004 p. 146)		
<i>Construction Camp Amendment Regulations 2013</i>	14 Nov 2013 p. 5031-2	r. 1 and 2: 14 Nov 2013 (see r. 2(a)); Regulations other than r. 1 and 2: 18 Nov 2013 (see r. 2(b) and <i>Gazette</i> 14 Nov 2013 p. 5027)

Defined terms

[This is a list of terms defined and the provisions where they are defined.

The list is not part of the law.]

Defined term	Provision(s)
ablutionary or sanitary caravan.....	28
artificial light	5, 28
construction camp	5, 28
dining caravan.....	28
dining room.....	5
effective air conditioning	5
effectively air conditioned	5
kitchen.....	5
kitchen caravan	28
occupier.....	5
office caravan.....	28
residential caravan	28
sleeping caravan.....	28
sleeping quarters	5
toilet compartment	28