

# Gazette Government

# WESTERN AUSTRALIA

(Published by Authority at 4 p.m.)

(REGISTERED AT THE GENERAL POST OFFICE. PERTH. FOR TRANSMISSION BY POST AS A NEWSPAPER.)

No. 86.1

PERTH: FRIDAY, 17th OCTOBER

[ 1958.

#### HEALTH ACT, 1911-1957.

Municipality of Narrogin.

P.H.D. 993/53, Ex. Co. No. 1961.

WHEREAS under the provisions of the Health Act, 1911-1957, the Governor may make Model By-laws for all or any of the purposes for which by-laws may be made by a local authority; and whereas Model By-laws described as Series "A," made by the Governor and amended from time to time, have been reprinted pursuant to the Reprinting of Regulations Act, 1954, in the Gazette on 9th August, 1956; and whereas a local authority may adopt such Model By-laws with or without modification: Now, therefore, the Municipality of Narrogin, being a local authority within the meaning of the Health Act, 1911-1957, doth hereby resolve and determine that the said reprinted Model By-laws shall be adopted with the following modifications:—

#### Part I-General Sanitary Provisions.

1. After By-law 14 insert a new By-law 14A as follows:-

## 14A.—Prescribed Area—Section 112A.

The area described in the schedule hereto is prescribed as an area within which every occupier shall-

- (a) not, unless he is authorised by the local authority so to do, remove any house and trade refuse from the premises; and
- (b) shall pay to the local authority or its contractor as the case may be, for the removal the prescribed charge or the charge according to the scale published in accordance with section one hundred and thirteen of the Health Act, 1911-1957.

### Schedule.

The Municipal District of Narrogin as constituted under the Municipal Corporations Act, 1906, as amended.

#### Part IX-Offensive Trades.

- 2 After By-law 14 in "Section A-General" add a new By-law 14A as follows:-
  - The occupier of every slaughterhouse within the district shall cause the premises to conform to the following conditions:-
    - (a) The killing pen shall be enclosed by walls at least nine inches thick which shall be constructed to a height of six feet above the floor or brickwork, stonework or concrete.